

Area of Application

ESSVE Decking screw Classic A4 is designed for the installation of fencing, decking timber, etc against wooden joists in very aggressive environments such as marine/off-shore environments, pool areas and structures below ground level.

NOTE! We always recommend pre-drilling for installation of hardwood decking timber, for example, Cumaru, Kirai, etc.

Description

The screw is made of stainless acid proof steel, SAE316, A4. It is equipped with 1 fibre

cut in the point, which minimises the risk of splintering and reduces the drive-in torque. The head is equipped with 6 cutting grooves that countersinks the screw during installation. The screw is fitted with Ph2-bit drive. ESSVE Decking screw Classic A4 are mounted on a plastic band intended for the most common autofeed screwdrivers e.g. Makita, Hilti, Senco etc.



Installation

Recommended rpm: approx. 1400 - 2500/min.

Specification

Material	Stainless acid proof steel A4
Surface treatment	Wax
Corrosion category	C5
Ultimate tensile strength value, f_{uk}	Min. 500 MPa
Yield point value, f_{yk}	Min. 250-300 MPa

Decking screw Classic for wooden joists, stainless steel A4

Technical data and packing

Item no.	Dimension dk x L mm	D mm	B mm	Bit no	Qty/ pack.	Pack./ large pack.
601342	4.2 x 42	7.4	27.0	Ph2	1000	6
601355	4.2 x 55	7.4	27.0	Ph2	1000	6

