

Area of application

ESSVE Galvanised band is designed for different types of installation, stabilisation and anchoring of timber structures and trusses.

Description

The band is made of cold-rolled, hot dip galvanized sheet steel with different hole pat-

terns and sizes.

Installation

The galvanised band is installed using e.g. ESSVE Anchor nails 4.0 mm or ESSVE Wood connector screws 5.0 mm.



Specification

Material	Cold rolled, sheet steel
Surface treatment	Hot dip galvanized 20 µm
Corrosion category	C2
Nail hole	See table
Length/pack.	See table

Galvanised band

Item no.	Dimensions mm	Hole Ø mm	Length/pack. m	Band type	Practical load capacity for the band kN	Qty/pack.	Quantity / pallet	Item code
396660843	12×0.7	5.5/3.2	10	2	1.0	1	672	L
396660508	13×0.7	5.5/3.2	10	2	1.0	1	672	L
5171325	13×0.7	5.5/3.2	25	2	1.0	1	486	L
396660730	20×0.7	7.0/5.0/3.2	25	2	1.2	1	223	L
396660706	20×0.7	8.5/6.5/4.5	10	2	1.0	1	456	L
396660805	20×1.0	7.0/5.0/3.2	10	2	2.0	1	456	L
396660839	25×1.2	8.5/6.5/4.2	25	1	3.5	1	180	L
396660904	25×1.5	8.5/6.5/4.2	10	2	2.0	1	385	L
396660938	25×2.0	8.5/6.5/4.5	10	1	6.0	1	150	L

